



# Classic Cars - Wallhanging

Designed by Deb Mosa

Finished Quilt Approximately: 42" x 52"

**Classic Cars** fabrics by Exclusively Quilters - Style #4065

An added 1/8 to 1/2 yard is added to all yardages to account for shrinkage, straightening, cutting errors and prints that may require special cutting to get the best results.

## **Fabric Requirements:** Based on 42" wide fabric

Two 2/3 yard **Classic Cars** panels (#61146)  
3/8 yard black (#61148-85)  
1/3 yard light blue (#61148-2)  
5/8 yard wheels (#60334-20)  
1 yard navy (61148-20)  
1-1/2 yards cars (#61147-2)  
2-3/4 yards fabric for backing (or 1-3/4 yards Wide Backing)  
48" x 58" quilt batting

## **Cutting Directions:** All measurements based on a 1/4" seam allowance.

From the *Vintage Cars* panels:

Trim six pillow panels each to 9-1/2" square

From the *black* fabric:

Cut five 1-1/2" x 42" strips, recut one strip into three 1-1/2" x 9-1/2" strips, cut from each of two strips cut a 1-1/2" x 19-1/2" strip (reserve remaining length of each strip)

From the *light blue* fabric:

Cut four 1-1/2" x 42" strips

From the *wheels* fabric:

Cut four 3" x 42" strips

From the *navy* fabric:

Cut five 2-1/2" x 42" strips for binding

Cut eight 1-1/2" x 42" strips for border

From the *cars* fabric:

Cut two 5-1/2" x length of fabric strips (parallel to the selvage)

Cut four 5-1/2" x remaining width of fabric (approx. 30" wide)

## **Sewing Directions:**

1. Lay out the six trimmed panels in three horizontal rows of two panels each. Stitch a 1-1/2" x 9-1/2" black strip between the panels of each horizontal row. Stitch the 1-1/2" x 19-1/2" black strips between the horizontal rows. Stitch a 1-1/2" x 42" black strip to right and left sides of quilt center. Press and trim excess from these and all successive sashing/border additions. Add remaining lengths of 1-1/2" black strips to the top and bottom of quilt center.
2. Stitch a 1-1/2" light blue strip to right and left sides of quilt center. Add 1-1/2" light blue strips to top and bottom.
3. Add 3" wheel border then a 1-1/2" navy border in the same manner as first border. Reserve excess navy strip to use on final border.
4. Stitch a 5-1/2" x length of fabric cars strips to right and left sides of quilt. Make two borders each with two 5-1/2" x remaining width of fabric cars strips then add to top and bottom of quilt.
5. Add longer reserved navy strip to two 1-1/2" x 42" navy strips. Add to sides of quilt. Add remaining reserved navy strips to two 1-1/2" x 42" navy strips and add to top and bottom of quilt.
6. Layer backing, batting and quilt top. Baste and quilt as desired. Trim backing and batting.
7. Make binding from five 2-1/2" navy strips and add to quilt.