



a Harbor Lights - Wallhanging b

Quilt by Deb Mosa

Finished Quilt Approximately: 41-1/2" x 53"

Harbor Lights fabrics by Exclusively Quilters - Style #3824

Fabric Requirements: Based on 44" wide fabric

One **Harbor Lights** panel (#60200-2)

1/2 yard navy (#60205-23)

1/2 yard cream (#60203-9)

3/4 yard tossed lighthouse (#60202-2)

1/2 yard red (#60205-1)

1-1/4 yards light blue (#60204-2)

1 yard blue (#60205-2)

3 yards fabric for backing (#60205-1 suggested)

46" x 58" quilt batting

An added 1/8 to 1/2 yard is added to all yardages to account for shrinkage, straightening, cutting errors and prints that may require special cutting to get the best results.

You should protect your investment in time and fabric by making sample blocks before cutting into your fabric because Exclusively Quilters will take no responsibility for replacing fabrics.

Shops who wish to kit this design are responsible for figuring yardage for their kits if they wish to reduce yardages.

Cutting Directions: All measurements based on a 1/4" seam allowance.

From the **Harbor Lights** panel:

Trim six pillow panels each to 11-1/2" square

From the **navy** fabric:

Cut five 1-1/2" x 44" strips, recut one strip into three 1-1/2" x 11-1/2" strips

Cut two 1-1/4" x 44" strips, trim each to 1-1/4" x 23-1/2" strips

From the **cream** fabric:

Cut three 3-1/4" x 44" strips, recut into twelve 3-1/4" x 2-7/8" and sixteen 3-1/4" x 3" pieces

From the **tossed lighthouse** fabric:

Cut five 3-1/4" x 44" strips

From the **red** fabric:

Cut three 3-1/4" x 44" strips, recut into twelve 3-1/4" x 2-7/8" and sixteen 3-1/4" x 3" pieces

From the **light blue** fabric:

Cut two 2-1/4" x *length of fabric* strips (parallel to the selvage)

Cut two 2-1/4" x *remaining width of fabric* (approx. 36" wide)

From the **blue** fabric:

Cut one 3-1/4" x 44" strip, recut into four 3-1/4" squares

Cut five 2-1/2" x 44" strips for binding

Cut five 1-1/2" x 44" strips for outside border

Sewing Directions:

1. Lay out the six trimmed panels in three horizontal rows of two panels each. Stitch a 1-1/2" x 11-1/2" navy strip between the panels of each horizontal row. Stitch the 1-1/4" x 23-1/2" navy strips between the horizontal rows. Stitch a 1-1/2" x 44" navy strip to right and left sides of quilt center. Press and trim excess from these and all successive border additions. Add remaining 1-1/2" navy strips to the top and bottom of quilt center.

2. Stitch a 2-1/4" x *length of fabric* light blue strips to right and left sides of quilt. Add the 2-1/4" x *remaining width of fabric* light blue strips to top and bottom of quilt.

Harbor Lights - Wallhanging

Page 2

3. Make two side borders each with eight red and eight cream 3" x 3-1/4" pieces. Stitch the pieces together, alternating red and cream, with pieces sewn together along the 3-1/4" edges (so the border is 3-1/4" wide before it is sewn onto the quilt). If the borders need to be sized to fit the sides of the quilt, increase or decrease the seam allowance on a few seams. Referring to the quilt layout, stitch the borders to right and left sides of quilt.
4. Make top and bottom borders each with six red, six cream 2-7/8" x 3-1/4", and two 3-1/4" blue pieces. Stitch the pieces together, alternating red and cream with a blue on each end, with pieces sewn together along the 3-1/4" edges (so the border is 3-1/4" wide before it is sewn onto the quilt). If the borders need to be sized to fit the quilt, increase or decrease the seam allowance on a few seams. Referring to the quilt layout, stitch the borders to top and bottom of quilt.
5. Cut one 3-1/4" tossed lighthouse strip into two equal lengths. Sew each half-length strip end-to-end with a full-length strip. Add these to the right and left sides of quilt. Stitch the remaining 3-1/4" tossed lighthouse strips to the top and bottom of quilt.
6. Make and add a 1-1/2" blue border in the same manner as the tossed lighthouse border.

Finishing:

1. Cut backing into two equal lengths. Sew the two lengths together along selvage edges. Layer the backing, batting and quilt top. Quilt or tie as desired.
2. Prepare binding from five 2-1/2" x 44" blue strips. Sew strips together into one long binding strip. Press strip in half lengthwise.
3. Carefully trim backing and batting even with quilt top.
4. Leaving an 8" tail of binding, sew binding to top of quilt through all layers matching all raw edges. Miter corners. Stop approximately 12" from where you started. Lay both loose ends of binding flat along quilt edge. Where these two loose ends meet, fold them back on themselves and press to form a crease. Using this crease as your stitching line, sew the two open ends of the binding together right sides together. Trim seam to 1/4" and press open. Finish sewing binding to quilt.
5. Turn binding to back of quilt and blind stitch in place.