

# Autumn Splendor

Quilt Designed by eQuilter



54" x 71"

**Skill Level:** Confident Beginner**Finished Quilt Size:** 54" x 71"*Please read all instructions before beginning. Pre-washing NOT recommended.*

## Yardages and Cutting

*WOF is 42" width of fabric from selvage edge to selvage edge. LOF is length of fabric, parallel to the selvage edges. Remove as little fabric as possible when trimming selvages and squaring strip ends.*

### 1 Autumn Splendor panel

- Trim to 22 1/2" x 39 1/2" keeping scene centered.

### 1 3/4 yards ombre print

- 2 strips 8" x WOF; trim to 42 1/2" for side borders.
- 1 strip 8" x remaining LOF from light edge and 1 strip 8" x LOF from dark edge; trim to 40 1/2" for top and bottom borders.

### 3/4 yard rust tonal

- 4 strips 2" x WOF; trim to (2) 2" x 25 1/2" and (2) 2" x 39 1/2" panel framing strips.
- 6 strips 2 1/2" x WOF for outer border.

### 1 yard green/teal tonal

- 6 strips 5 1/2" x WOF for borders.

### 3/4 yard leaf print

- 7 strips 2 1/4" x WOF for binding.

### 4 yards of 42" backing fabric OR

### 5 yards of 42" directional fabric

- 2 strips 69" x WOF OR
  - 2 strips 86" x WOF for directional fabric
- OR

### 2 yards wide backing fabric

- 1 piece 69" x 86"

### Batting

- 1 piece 69" x 86"

## Completing the Quilt

*Use a 1/4" seam allowance for all piecing. Press seams as directed. Refer to the exploded quilt diagram as needed.*

1. Sew the 2" x 39 1/2" rust tonal strips to the long sides of the panel. Press seams toward the strips. Stitch the 2" x 25 1/2" rust tonal strips to the top and bottom of the panel. Press seams toward the strips.
2. Sew the 8" x 42 1/2" ombre print strips to the long sides of the framed panel. Press seams toward the strips. Stitch the 8" x 40 1/2" light ombre print strip to the top of the framed panel and the dark ombre print strip to the bottom. Press seams toward the strips. Note: the light and dark ombre print strips may blend better with the side ombre print strips if they are turned 180 degrees.
3. Sew the 5 1/2" x WOF green/teal tonal strips short ends together to make a long strip. Press seams to one side. Cut into 2 strips each 50 1/2" and 57 1/2". Stitch the longer strips to the sides of the quilt center and the shorter strips to the top and bottom. Press seams toward the strips.
4. Sew the 2 1/2" x WOF rust tonal strips short ends together to make a long strip. Press seams to one side. Cut into 2 strips each 54 1/2" and 67 1/2". Stitch the longer strips to the sides of the quilt center and the shorter strips to the top and bottom. Press seams toward the strips.
5. If using 42" backing fabric, remove the selvage edges from the backing pieces. Join the pieces on the long edges with a 1/2" seam allowance. Press seam open. Trim to make a 69" x 86" backing piece.
6. Layer the quilt top with the backing and batting pieces. Quilt as desired. Trim batting and backing even with the top.
7. Join the leaf print binding strips on the short ends with diagonal seams to make a long strip. Press seams in one direction. Press the strip in half along the length with wrong sides together. Bind the quilt edges using your favorite method to complete the quilt.



**Exploded Quilt Diagram**