
Greeting the Moon

by Keiichi Nishimura

Designed and pieced by June Pease • Machine quilted by Tracy Szanto



FABRIC REQUIREMENTS:

A. Pattern #25166 – MUL1		1 panel
B. Pattern #25167 – MUL1		3/8 yard
C. Pattern #25168 – DKGRY1		5/8 yard
D. Pattern #25169 - GRY1		2 yards
E. Pattern #25170 – RED1	(red tonal)	¹/₄ yard
F. Pattern #25170 – BLA1	(black tonal)	1³/8 yards
G. Pattern #25171 – CRE1		1 yard
H. Pattern #25171 – BEI1	(ivory tonal)	¹/2 yard
I. Pattern #25171 – RED1	(red tonal)	¹/₂ yard
Fusible interfacing (lightweigh	nt)	¹/₂ yard
Fusible interfacing (lightweigh Backing (2-1/4 yards w	ide backing)	3 ³ / ₄ yards
Batting		

CUTTING INSTRUCTIONS:

Please read all instructions carefully before beginning. ½" seam allowance is included in measurements and all strips are cut across the width of the fabric unless noted otherwise. Cut in order given, label pieces and keep together until ready to sew.

- A. Pattern #25166 MUL1 (panel):
 - 1. Cut the crane panel to measure $23^{1}/_{2}$ " x $42^{1}/_{2}$ ".
- TIP: The instructions that follow for Fabrics B, C, D, E, F, G and H (Borders #1 #6) indicate cutting a specified number of strips, sewing strips together and cutting to specific lengths. It is advised to cut the number of strips indicated below, but to wait until you get to the step for each border to piece and crosscut the strips. Variances in the size of the panel and seam allowances may vary the sizes of crosscuts required.
- B. Pattern #25167 MUL1 (cranes):
 - 1. Cut five $2" \times 40"$ strips. Sub-cut two $2" \times 28^{1}/2"$ strips for top and bottom borders. Sew together remaining strips with diagonal seams and sub-cut two $2" \times 44^{1}/2"$ strips for the side borders.
- C. Pattern #25168 DKGRY1 (floral and feathers):
 - 1. Cut seven $2^1/2^{\shortparallel}$ x 40" strips. Sew together with diagonal seams. Sub-cut two $2^1/2^{\shortparallel}$ x $52^1/2^{\shortparallel}$ strips for top and bottom borders and sub-cut two $2^1/2^{\shortparallel}$ x $68^1/2^{\shortparallel}$ strips for the side borders.
- D. Pattern #25169 GRY1 (swirl):
 - 1. Cut two $9^{1}/_{2}$ " x 40" strips across the width of the fabric. Sub-cut two $9^{1}/_{2}$ " x 33" strips for top and bottom borders.
 - 2. Cut one $11^{1}/_{2}$ " x $47^{1}/_{2}$ " strip on the length of the fabric for the right side border (as you face the quilt).
- E. Pattern #25170 RED1 (texture):
 - 1. Cut four $1^{1}/_{2}$ " x 40" strips. Sub-cut two $1^{1}/_{2}$ " x $26^{1}/_{2}$ "

- strips for the top and bottom borders and sub-cut two $1^{1}/_{2}$ " x $42^{1}/_{2}$ " strips for the side borders, piecing strips if needed.
- F. Pattern #25170 BLA1 (texture):
 - 1. Cut seven $3^{1}/_{2}$ " x 40" strips. Sew together with diagonal seams. Sub-cut two $3^{1}/_{2}$ " x $58^{1}/_{2}$ " strips for the top and bottom borders and sub-cut two $3^{1}/_{2}$ " x $72^{1}/_{2}$ " strips for the side borders.
 - 2. Cut eight $2^{1}/_{2}$ " x 40" strips for the binding.
- G. Pattern #25171 CRE1 (geometric):
 - 1. Cut two $9^{1}/2^{11}$ x 40" strips. Sew together with diagonal seams and sub-cut two $9^{1}/2^{11}$ x 14" strips for top and bottom borders and sub-cut one $7^{1}/2^{11}$ x $47^{11}/2^{11}$ strip for the left side border (as you face the quilt).
 - 2. Cut two $4^{1}/_{2}$ " x 40" strips. Sub-cut ten $4^{1}/_{2}$ " squares for appliqué.
- H. Pattern # 25171 BEI1 (geometric):
 - 1. Cut two 4¹/₂" x 40" strips. Sub-cut ten 4¹/₂" squares for appliqué.
- I. Pattern # 25171 RED1 (geometric):
 - 1. Cut six 2" x 40" strips. Sew together with diagonal seams. Sub-cut two 2" x $48^{1}/_{2}$ " strips for top and bottom borders and sub-cut two 2" x $65^{1}/_{2}$ " strips for the side borders.

PIECING INSTRUCTIONS:

Press toward the darker fabric when assembling.

A. Applique Block Assembly:

- 1. Place one 41/2" Fabric H square and one 41/2" Fabric G square right sides together. Sew 1/4" seam. Press seam to darker fabric.
- 2. Repeat Step 1 to make ten H/G units.
- 3. Sew two H/G units together to make a 9" Four Patch block. Make five Four Patch Blocks (Figure 1).
- 4. Make an 8" circle template. Trace five 8" circles with a permanent pen onto the smooth side of the fusible interfacing leaving space between the circles. The line is your sewing line. Rough cut the circles (Figure 2). Full size circle template available in the web version of this pattern at: www.redroosterfabrics.com.
- 5. The fusible interfacing helps to adhere the circles to the quilt but it also helps to line the circle so that the dark fabric does not show through to the light circle.



Figure 1 Make 5.



Figure 2 Make 5.

- 6. The right side of the fusible interfacing is the rough side/fusible side.
- 7. Place right side of Four Patch Block with the right side of the interfacing and sew the circle along the drawn line on the interfacing. Cut out, leaving a scant 1/4" seam allowance.
- 8. Pinch the fusible interfacing and cut a slit with scissors. Make the slit large enough to turn the circles right side out.
- 9. <u>Finger press</u> the edge of the circles. <u>No ironing</u> or the circles will adhere to the ironing surface.

QUILT ASSEMBLY:

Refer to Quilt Diagram and photo while assembling. Border #1:

 Sew the 1¹/₂" x 42¹/₂" Fabric E strips to each side of crane panel. Press seams toward border. Sew the 1¹/₂" x 25¹/₂" Fabric E strips to top and bottom border of crane panel. Press seams to border.

Border #2:

1. Sew the $2" \times 44^{1/2}"$ Fabric B strips to each side of quilt. Press seams to border. Sew the $2" \times 28^{1/2}"$ Fabric B strips to top and bottom of quilt. Press seams to border.

Border #3:

- 1. Sew the 7½" x 47½" Fabric *G* strip to the left side of the quilt. Press seam to border. Sew the 11½" x 47½" Fabric D strip to the right side of the quilt. Press seam to border.
- 2. Sew the 9½" x 14" Fabric G strips to the 9½" x 33" Fabric D strips, right sides together, making two 9½" x 45½" strips for the top and bottom borders. Press seams toward dark fabric. Sew to top and bottom of quilt. Press seams to borders.

Border #4:

1. Sew the 2" x 65½" Fabric I strips to each side of quilt. Press seams to border. Sew the 2" x 48½" Fabric I strips to the top and bottom of quilt. Press seams toward border.

Border #5:

1. Sew the 2½" x 68½" Fabric C strips to each side of quilt. Press seams to border. Sew the 2½" x 52½" Fabric C strips to the top and bottom of quilt. Press seams to border.

Border #6:


1. Sew the $3^1/2^n \times 72^1/2^n$ Fabric F strips to each side of the quilt. Press seams to border. Sew the $3^1/2^n \times 58^1/2^n$ Fabric F strips to the top and bottom of quilt. Press seams to border.


Appliqué Circles:

- 1. Use the photos of the quilt as a guide for laying out the circle appliqués. When you are pleased with the placement press them in place using a hot iron.
- 2. Use your favorite method of appliqué to stitch the circles to the quilt.

FINISHING:

- Prepare backing with a horizontal seam to measure 64" x 84".
- 2. Layer backing, batting, and quilt top. Baste layers together.
- 3. Quilt as desired.
- 4. Trim layers even with the top.
- 5. Join binding strips together with diagonal seams. Attach to quilt using your favorite method.
- 6. Make a label and sew to back of quilt.





©2015 Red Rooster Fabrics. All rights reserved. Not intended for individual resale. The design for this Red Rooster Fabrics' pattern is protected by U.S. copyright law. Quilt stores: for additional copies of this pattern please call or write Red Rooster Fabrics at the address listed: 253 West 35th Street, 11th Floor, New York, NY 10001 • 800.742.2459 www.redroosterfabrics.com

We take great care to ensure that the information included in our free pattern is accurate and presented in good faith. No warranty is provided nor results guaranteed. For your convenience, we post an up-to-date listing of corrections on our website: http://www.redroosterfabrics.com/quilt/oops.php If a correction is not noted, please contact our customer service department at customerservice@redroosterfabrics.com. You may also call or write us at the address below.