

# Gilded Klimt Kitty

Quilt Designed by eQuilter



69" x 77"

Skill Level: Intermediate

Finished Quilt Size: 69" x 77"

*Please read all instructions before beginning. Pre-washing NOT recommended.*

## Yardages and Cutting

*WOF is width of fabric from selvage edge to selvage edge. Remove as little fabric as possible when squaring strip ends.*

### Klimt Kitty Large panel

- Trim to 34 1/2" wide x 42 1/2" tall, keeping the framing even.

### 2 yards Klimt Kitty allover

- Fussy-cut (8) 13" squares, centering on kitties.

### 1 yard Klimt patch print

- 3 strips 10 1/2" x WOF; cut into (8) 10 1/2" squares.

### 3/4 yard multicolor print

- 9 strips 2 1/4" x WOF for binding.

### 3 1/2 yards black solid

- 4 strips 2 1/2" x WOF; cut into (2) strips each, 42 1/2" and 38 1/2".
- 5 strips 5 1/2" x WOF; cut into to (32) 5 1/2" squares.
- 2 strips 1 7/8" x WOF; cut into (8) strips 1 7/8" x 10 1/2".
- 2 strips 3 7/8", cut into (8) strips 3 7/8" x 10 1/2".
- 3 strips 1 3/4", cut into 8 strips 1 3/4" x 13 1/4".
- 4 strips 1 3/4", cut into 8 strips 1 3/4" x 17 1/4".
- 4 strips 6 3/4", cut into 24 squares 6 3/4" x 6 3/4".
- 7 strips 3 1/2" x WOF for outer border.

### 5 1/4 yards of 44/45" backing fabric

- 2 strips 92" x WOF

OR

### 2 1/2 yards wide backing fabric

- 1 piece 84" x 92"





### Batting

- 1 piece 84" x 92"

## Completing the Quilt

*Use a 1/4" seam allowance for all stitching. Press seams as directed. Refer to the exploded quilt diagram as needed.*

1. Draw a diagonal line from corner to corner on the wrong side of the 5 1/2" black squares and 6 3/4" black squares.
2. Place marked 5 1/2" squares right sides together on the top left and bottom right corners of the Klimt patch print squares. Sew on the lines, trim seam allowance 1/4" out from the stitching. Press the black triangles open with seam allowance toward the triangles. Repeat on the remaining corners of the horse print squares to make 10 1/2" x 10 1/2" horse units **except** press seam allowances away from the black triangles.




**Make 12 Klimt patch units**

3. Repeat step 2 with (16) 6 3/4" black squares on (4) 13" Klimt Kitty squares to make 4 Klimt Kitty diamond units.



**Make 4 Klimt Kitty diamond units**

Place (4) 6 3/4" black squares right sides together on the top left and bottom right corners of (2) 13" Klimt Kitty squares. Repeat with remaining (4) 6 3/4" black squares on the top right and bottom left corners of the remaining (2) 13" Klimt Kitty squares. Sew on the lines, trim seam allowance 1/4" out from the stitching. Press the black triangles open with seam allowance toward the triangles to make (4) Klimt Kitty corner blocks.



**Make 4 Klimt Kitty corner blocks (2 of each shown)**

4. Stitch 2 1/2" x 42 1/2" black strips to the sides of the large panel. Sew 2 1/2" x 38 1/2" to the top and bottom. Press seams toward the strips.

5. Sew 3 7/8" x 10 1/2" black strips to the top and bottom of a Klimt patch unit. Then stitch 1 3/4" x 17 1/4" black strips to the sides. Press seams toward the strips. Repeat to make (4) large patch units.

6. Sew 1 7/8" x 10 1/2" black strips to the sides of a Klimt patch unit. Then stitch 1 3/4" x 13 1/4" black strips to the top and bottom. Press seams toward the strips. Repeat to make (4) small patch units.

7. Sew (2) large patch units to the top and bottom of a Klimt Kitty diamond unit to make a 13" x 46 1/2" side strip. Press seams open. Repeat to make a second side strip. Stitch to the sides of the framed panel. Press seams toward the framed panel.

8. Sew (2) small patch units to the sides of a Klimt Kitty diamond unit. Then sew Klimt Kitty corner blocks to the sides (paying close attention to the orientation of the corner blocks on the exploded diagram), to make a 63 1/2" x 13" top strip. Press seams open. Repeat to make a bottom strip (again paying close attention to the orientation of the corner blocks on the exploded diagram). Stitch to the top and bottom of the framed panel. Press seams toward the framed panel.

9. Stitch the 3 1/2" x WOF black strips short ends together to make a long strip. Press seams to one side. Cut into (2) strips each, 71 1/2" and 69 1/2". Sew the 71 1/2" strips to the sides of the quilt center and the 69 1/2" strips to the top and bottom to complete the top. Press seams toward the strips.

10. If using 44/45" backing fabric, remove the selvage edges from the backing pieces. Join the pieces on the long edges with a 1/2" seam allowance. Press seam open. Trim to make the 84" x 92" backing piece.

11. Layer the quilt top with the backing and batting pieces. Quilt as desired. Trim batting and backing even with the top.

12. Join the multicolor print binding strips on the short ends with diagonal seams to make a long strip. Press seams in one direction. Press the strip in half along the length with wrong sides together. Bind the quilt edges using your favorite method to complete the quilt.

